

Réf : ECA001

ÉLINGUE CÂBLE 1 BRIN BOUCLES NUES MANCHONNÉES ALU



Diamètre du Câble mm	CMU en kg facteur M= 1			CMU en kg facteur M= 2			Passage boucle mm
	AT-1770	AM-1770	AM-1960	AT-1770	AM-1770	AM-1960	
8	700	740	820	1400	1480	1640	120 x 60
9	850	930	1000	1700	1860	2000	135 x 68
10	1050	1200	1300	2100	2400	2600	150 x 75
11	1300	1400	1500	2600	2800	3000	165 x 83
12	1550	1600	1800	3100	3200	3600	180 x 90
13	1800	1900	2100	3600	3800	4200	195 x 98
14	2120	2300	2500	4240	4600	5000	210 x 105
16	2700	2900	3300	5400	5800	6600	240 x 120
18	3400	3700	4100	6800	7400	8200	270 x 135
20	4350	4600	4700	8700	9200	9400	300 x 150
22	5200	5600	6200	10400	11200	12400	330 x 165
24	6300	6600	7400	12600	13200	14800	360 x 180
26	7200	7800	8600	14400	15600	17200	390 x 195
28	8400	9000	10000	16800	18000	20000	420 x 210
30	10000	10400	11500	20000	20800	23000	450 x 225
32	11000	11830	13000	22000	23660	26000	480 x 240
34	12500	13300	14800	25000	26600	29600	510 x 255
36	14000	14900	16500	28000	29800	33000	540 x 270

Réf : ECA002

ÉLINGUE CÂBLE 1 BRIN BOUCLES COSSÉES MANCHONNÉES ALU



Diamètre du Câble mm	CMU en kg facteur M= 1			CMU en kg facteur M= 2			Passage boucle mm
	AT-1770	AM-1770	AM-1960	AT-1770	AM-1770	AM-1960	
8	700	740	820	1400	1480	1640	32 x 22
9	850	930	1000	1700	1860	2000	38 x 27
10	1050	1200	1300	2100	2400	2600	38 x 27
11	1300	1400	1500	2600	2800	3000	48 x 32
12	1550	1600	1800	3100	3200	3600	48 x 32
13	1800	1900	2100	3600	3800	4200	63 x 40
14	2120	2300	2500	4240	4600	5000	63 x 40
16	2700	2900	3300	5400	5800	6600	68 x 45
18	3400	3700	4100	6800	7400	8200	75 x 48
20	4350	4600	4700	8700	9200	9400	77 x 52
22	5200	5600	6200	10400	11200	12400	86 x 53
24	6300	6600	7400	12600	13200	14800	90 x 56
26	7200	7800	8600	14400	15600	17200	95 x 62
28	8400	9000	10000	16800	18000	20000	105 x 66
30	10000	10400	11500	20000	20800	23000	175 x 140
32	11000	11830	13000	22000	23660	26000	175 x 140
34	12500	13300	14800	25000	26600	29600	220 x 165
36	14000	14900	16500	28000	29800	33000	220 x 165