

Réf : ECA004A

ÉLINGUE CÂBLE FERMÉE MANCHONNÉES ALU



Diamètre du Câble mm	CMU en kg facteur M = 1*			CMU en kg facteur M = 2**		
	AT-1770	AM-1770	AM-1960	AT-1770	AM-1770	AM-1960
8	1400	1480	1640	2800	2960	3280
9	1700	1860	2000	3400	3720	4000
10	2100	2300	2560	4200	4600	5120
12	3100	3300	3660	6200	6600	7320
13	3600	3800	4200	7200	7600	8400
14	4240	4500	5000	8480	9000	10000
16	5400	5900	6500	10800	11800	13000
18	6800	7480	8300	13600	14960	16600
20	8700	9200	9400	17400	18400	18800
22	10400	11000	12380	20800	22000	24760
24	12600	13300	14700	25200	26600	29400
26	14400	15600	17300	28800	31200	34600
28	16800	18000	20000	33600	36000	40000
30	20000	20800	23000	40000	41600	46000
32	22000	23600	26200	44000	47200	52400
34	25000	26600	29600	50000	53200	59200
36	28000	29900	33100	56000	58800	66200

Réf : ECA004A

Élingue de Sécurité " Anti—Fouet "



Diamètre du Câble mm	Long (cm)	CMU:KN
4	50	10.40
5	60	16.3
6	100	21.2
10	100	63