



Elingues Rondes

Fabriqué conformément à la Norme EN 1492-2+A1



		C.M.U. avec 1 seule élingue ronde (kg)							C.M.U. avec 2 élingues rondes (kg)			
		simple direct	Nœud coulant	Angle d'inclinaison				Angle d'inclinaison				
				0° à 7°	7° à 45°	45° à 60°	7° à 45°	45° à 60°	7° à 45°	7° à 45°	45° à 60°	45 °à 60°
MODE D'ÉLINGAGE												
		Coefficient										
		1,0	0,8	2,0	1,4	1,0	0,7	0,5	1,4	1,1	1,0	0,8
CMU	COULEUR	CMU X Coefficient										
1 t	VIOLET	1000	800	2000	1400	1000	700	500	1400	1120	1000	800
2 t	VERT	2000	1600	4000	2800	2000	1400	1000	2800	2240	2000	1600
3 t	JAUNE	3000	2400	6000	4200	3000	2100	1500	4200	3360	3000	2400
4 t	GRIS	4000	3200	8000	4500	4000	2800	2000	5600	4480	4000	3200
5 t	ROUGE	5000	4000	10000	7000	5000	3500	2500	7000	5600	5000	4000
6 t	MARRON	6000	4800	12000	8400	6000	4200	3000	8400	6720	6000	4800
8 t	BLEU	8000	6400	16000	11200	8000	5600	4000	11200	8960	8000	6400
10 t	ORANGE	10000	8000	20000	14000	10000	7000	5000	14000	11200	10000	8000
12 t	ORANGE	12000	9600	24000	16800	12000	8400	6000	16800	13440	12000	9600
15 t	ORANGE	15000	12000	30000	21000	15000	10500	7500	21000	16500	15000	12000
20 t	ORANGE	20000	16000	40000	28000	20000	14000	10000	28000	22400	20000	16000
30 t	ORANGE	30000	24000	60000	42000	30000	21000	15000	42000	33000	30000	24000
40 t	ORANGE	40000	32000	80000	56000	40000	28000	20000	56000	44000	40000	32000
50 t	ORANGE	50000	40000	100000	70000	50000	35000	25000	70000	55000	50000	40000

