


Réf : G19X7 1960C


CABLE ANTIGIRATOIRE ACIER GALVANISÉ 19 TORONS DE 7 FILS (1 + 6), 1960 N/mm².



Item	Diamètre du câble (mm)	Rupture KN
01	6	23.10
02	8	41.10
03	9	52.10
04	10	64.3
05	11	77.8
06	12	92.60
07	13	109
08	14	126
09	15	145
10	16	165
11	18	208
12	20	257
13	22	311

Réf : 6x36AMAP


CABLE ACIER CLAIRE 6 TORONS DE 36 FILS (14+7/7+7+1). Âme Métallique.



Item	Diamètre du câble (inch)	Rupture KN
01	1/4	30.00
02	5/16	46.50
03	3/8	67.00
04	7/16	90.30
05	1/2	118.20
06	9/16	149.30
07	5/8	183
08	3/4	260
09	7/8	354
10	1	462
11	1 1/8	585
12	1 1/4	710

Réf : G35X7 2160C


CABLE ANTIGIRATOIRE ACIER GALVANISÉ 35 TORONS DE 7 FILS (1 + 6), 2160 N/mm².



Item	Diamètre du câble (mm)	Rupture KN
01	13	131
02	14	152
03	15	175
04	16	199
05	17	225
06	18	252
07	19	280
08	20	311
09	21	343
10	22	376
11	24	448
12	26	526
13	28	610
14	30	700
15	32	796

Réf : G35X7 2160CO

CABLE ANTIGIRATOIRE ACIER GALVANISÉ COMPACTE 35 TORONS DE 7 FILS (1 + 6), 2160 N/mm².



Item	Diamètre du câble (mm)	Rupture KN
01	13	150
02	14	174
03	15	199
04	16	227
05	17	256
06	18	286
07	19	319
08	20	354
09	21	390
10	22	428.7
11	23	468